

# Service Head Adapter Flex Riser



- All-flex riser for fast, easy hookup
- Ideal for both natural gas and propane riser applications.
- Provides one continuous PE pipe service from service main or LP tank to home.

## STANDARD LENGTHS

- 36" or 48" for home or yard connections.
- 84" for one continuous line from the LP tank (first stage regulator) to below-ground service.

## Benefits

- Quick and easy assembly with pipe or crescent wrench.
- Leak-resistant service adapter design.
- Self-seating design reduces need for torque measurement.
- Reduces assembly labor and eliminates need for costly welding or fusing equipment.
- Rust and corrosion protection through zinc plated internal and external surfaces.
- Flexible case manufactured with UV protected material.

For the full scope of testing procedures and resulting data, please request a copy of the Technical Data Package (TDP) from your Lyall sales representative or Customer Service.

## Lyall Quality

- Lyall is an ISO 9001 registered manufacturing facility that employs a robust quality control system.
- The steel to PE joint meets ASTM F1948 requirements.
- The flex tubing meets Section 4.2.2 of ASTM 1973 requirements.
- The joint between the flex tubing and service head adapter meets Section 6.11 of ASTM 1973 requirements.
- Listed with IAPMO/UPC

**CUSTOMER SERVICE** | (800) 535-9255 | [RWLyall.com](http://RWLyall.com)

LIT-SHAFRDS-1G

