



Continental CCS Tracer Wire




Our Continental tracer wire brand is designed to withstand damage from sharp objects and harsh environments, while offering some of the highest break loads in the industry. Our tracer wire consists of a hard-drawn 12 or 14* AWG Copper Clad Steel conductor insulated with a high-density polyethylene .030 mil jacket. Further, our wire construction provides a strong locating signal to ensure consistent, reliable performance. Our Continental tracer wire brand is the superior tracer wire choice for your demanding field applications. *10 AWG available upon request.

Features

- Highest copper clad steel tracer wire break load available.
- Significantly lower in cost & great price stability versus copper.
- Conductor is equal to copper in signal tracing performance.
- Available in 500' and 2500' spools.
- Made in America

CONDUCTOR SIZE	12 AWG Copper Clad Steel	14 AWG Copper Clad Steel
ITEM NUMBER	33-7701-01	33-7700-01
STRANDING	Solid	Solid
INSULATING MATERIAL	PE-High Density	PE-High Density
INSULATING THICKNESS	0.030" Nominal	0.030" Nominal
FINISHED O.D.	0.142" Nominal	0.126" Nominal
WEIGHT (PER 1000 FT.)	22.03 lbs./1000	14.85 lbs/1000
TEMPERATURE RATING	-20°C to 80°C	-20°C to 80°C
OPERATING VOLTAGE	30v	30v
INSULATION COLOR	Yellow-Gas	Yellow-Gas
RATE BREAK LOAD	282-299 lb.	175-177 lb.
RATED TENSILE STRENGTH	55,000-58,111 PSI	54,251-55,000 PSI

Other insulating colors are available; Blue, Red and Green.



The Ultimate Connection



1-800-558-1373 or FAX 1-800-788-1668 • Visit www.conind.com

99-1069-Lyall 05/2016



Continental Copper Tracer Wire




Our Continental tracer wire brand is designed to perform in harsh environments where protection from sharp, abrasive, and corrosive soil conditions is important. Our solid copper tracer wire is manufactured from a soft drawn copper conductor in 12 or 14* AWG with a high-density polyethylene .030 mil jacket. This solid copper construction offers the ease of workability while combining the strength of a quality HDPE jacket. Further, our solid copper wire performs reliably in field applications where signal strength and locating accuracy are critical. Choose the Continental tracer wire brand for your tracer wire needs! *10 AWG available upon request.

Features

- Highest copper tracer wire break load available.
- Superior tracing performance.
- Available in 500' and 2500' spools.
- Made in America

CONDUCTOR SIZE	12 AWG Copper	14 AWG Copper
ITEM NUMBER	33-7699-01	33-7692-01
STRANDING	Solid	Solid
INSULATING MATERIAL	PE-High Density	PE-High Density
INSULATING THICKNESS	0.030" Nominal	0.030" Nominal
FINISHED O.D.	0.142" Nominal	0.126" Nominal
WEIGHT (PER 1000 FT.)	24.03 lbs./1000	16.11 lbs/1000
TEMPERATURE RATING	-20°C to 80°C	-20°C to 80°C
OPERATING VOLTAGE	30v	30v
INSULATION COLOR	Yellow-Gas	Yellow-Gas
RATE BREAK LOAD	165 lb.	104 lb.
RATED TENSILE STRENGTH	32,179 PSI	32,228 PSI

Other insulating colors are available; Blue, Red and Green.



The Ultimate Connection



1-800-558-1373 or FAX 1-800-788-1668 • Visit www.conind.com